

## **Internal Battery Pack**

## BC24V9AH / BC36V9AH / BC48V9AH / BC72V9AH

The ATEN UPS Internal Battery Pack comes with a hot-swap design, allowing uninterrupted operations during battery replacement to ATEN UPS systems. It ensures stable power supply and offers easy installation, bringing users hassle-free management to their power equipment.







BC24V9AH / BC36V9AH

BC48V9AH

BC72V9AH

## **Specifications**

|                                      | BC24V9AH  | BC36V9AH                | BC48V9AH                | BC72V9AH                |
|--------------------------------------|---|-------------------------|-------------------------|-------------------------|
| Electrical                           |   |                         |                         |                         |
| Nominal Output Voltage               | 24V   | 36V                     | 48V                     | 72V                     |
| Battery                              |   |                         |                         |                         |
| Battery Type                         | Sealed Lead-Acid  |                         |                         |                         |
| Battery Size                         | 9Ah   |                         |                         |                         |
| Battery Quantity                     | 2   | 3                       | 4                       | 6                       |
| Physical Properties                  |   |                         |                         |                         |
| Dimensions (L x W × H)               | 25.77 x 21.37 x 6.66 cm   | 25.77 x 21.37 x 6.66 cm | 32.50 x 20.40 x 6.66 cm | 47.60 x 20.40 x 6.66 cm |
| Weight                               | 5.70 kg   | 8.10 kg                 | 10.80 kg                | 15.90 kg                |
| Color                                | Black   |                         |                         |                         |
| Environmental                        |   |                         |                         |                         |
| Temperature<br>(Operating / Storage) | Operating: 32 – 104 °F (0 – 40 °C)<br>Storage: -15 – 45 °C                              |                         |                         |                         |
| Humidity<br>(Operating & Storage)    | 0 – 95%   |                         |                         |                         |
| Elevation<br>(Operating / Storage)   | Operating: 0 – 10,000 ft (0 – 3,000 meter)<br>Storage: 0 – 50,000 ft (0 – 15,000 meter) |                         |                         |                         |

www.aten.com E-mail: marketing@aten.com

3F., No.125, Sec. 2, Datung Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

Product information is subject to change without prior notice.

