



# kramer

## BC-2Sxx/LSHF

Speaker Bulk Cable – Low Smoke & Halogen Free

| Speakers



Kramer's BC-2Sxx/LSHF is a high-quality low-smoke, halogen free twisted pair cable designed for connecting speakers and amplifiers in commercial or residential AV systems

### FEATURES

**Quality Construction** - Rugged and flexible jacket with sequential markings every meter

**High Performance** - Use anywhere an unshielded stranded pair is suitable

**Length** - Available in reels of 300m (985ft)



# kramer

## TECHNICAL SPECIFICATIONS

---

CONSTRUCTION	<p>Conductors: BC-2S12/LSHF 12AWG (65/0.254); BC-2S14/LSHF 14AWG (41/0.254); BC-2S16/LSHF 16AWG (26/30) bare copper</p> <p>Insulation: Polypropylene color coded: red, black</p> <p>Outer Jacket Color: Light gray with blue lettering</p> <p>Outer Jacket: LSHF</p>
DIAMETERS	<p>Center Conductor: BC-2S12/LSHF 2.36mm (0.093in); BC-2S14/LSHF 1.87mm (0.074in); BC-2S16/LSHF 1.478mm (0.058in) bare copper</p> <p>PVC Insulation: BC-2S12/LSHF 3.2mm (0.126in); BC-2S14/LSHF 2.5mm (0.099in); BC-2S16/LSHF 2.0mm (0.079in)</p> <p>Outer Jacket: BC-2S12/LSHF 7.5mm (0.296in); BC-2S14/LSHF 6.6mm (0.260in); BC-2S16/LSHF 5.2mm (0.205in)</p>
ELECTRICAL	<p>DC Resistance: BC-2S12/LSHF 5.64<math>\Omega</math>/km (1.7<math>\Omega</math>/1000ft); BC-2S14/LSHF 8.9<math>\Omega</math>/km (2.7<math>\Omega</math>/1000ft); BC-2S16/LSHF 13.7<math>\Omega</math>/km (4.17<math>\Omega</math>/1000ft)</p> <p>Temperature: -20° to 75°C (-4° to 167°F)</p>
REGULATORY	<p>UL: CM</p> <p>CSA: CM, FT4</p> <p>RoHS: In compliance with European directive 2002/95/IEC</p> <p>DIN &amp; EU Equivalent: EN 50265-1:1998 EN 50265-2-1:1998 EN 50267-2-1:1998 EN 50267-2-2:1998</p>



# kramer

## CONFIGURATIONS

---

BC-2S12/LSHF-300M Speaker Cable 12AWG - Low Smoke & Halogen Free

---

BC-2S14/LSHF-300M Speaker Cable 14AWG - Low Smoke & Halogen Free

---