



DGKat-OUT8-F64

8-Channel HDMI & RS-232 over DGKat
Output Card

| DGKat



DGKat-OUT8-F64 is an eight-channel HDMI and RS-232 over DGKat twisted pair output card for the VS-6464 Series Modular Multi-Format Digital Matrix Switchers. The DGKat-OUT8-F64 outputs eight HDMI and RS-232 signals from the chassis

FEATURES

Max. Data Rate - 4.95Gbps

System Range - Up to 90m (295ft) at 1080i @60hz or up to 70m (230ft) at 1080p @ 60hz when using Kramer DGKat cables. Note: Transmission range depends on the signal resolution, graphics card and display used. If using third-party shielded CAT cables, both ends of the shield must be soldered to the connectors for the products to function properly

HDMI and HDCP Compliant

DGKat™ Signal Integration

3D Pass-Through

Bidirectional Local RS-232 Port

Kramer Equalization & re-Klocking Technology

Power Connect System - For supplying power to compatible TP receivers



KRAMER

TECHNICAL SPECIFICATIONS

OUTPUTS	8 TP ports on RJ-45 connectors, 8 serial ports on 3-pin terminal blocks
BANDWIDTH PER CHANNEL:	Video: 1.65Gbps; serial data: 19200
TOTAL BANDWIDTH:	Video: 4.95Gbps; serial data: 19200
MAXIMUM RANGE:	90m (300ft) – 1080i@60Hz
Power Consumption	45W
3D PASS THROUGH:	Supported
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
DIMENSIONS:	19cm x 13cm x 2cm (7.5" x 5.1" x 0.8") W, D, H
PRODUCT WEIGHT:	0.16kg (0.51lbs) approx
SHIPPING WEIGHT:	0.37kg (0.82lbs) approx
STANDARD COMPLIANCE:	HDCP 1.4, HDMI 1.3a
SAFETY REGULATORY COMPLIANCE:	CE, FCC
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
INCLUDED ACCESSORIES:	Screwdriver