

Product information "2-piece XLR connector set female + male 3 pin black solder version"

XLR cable set female and male with three contacts and a well-shaped and robust knob for a better user experience.

The 3-pin XLR Connector features a triple positioned clamp to prevent the inner cable from being twisted and broken.

This removable clamp is designed for multiple cable types

Remove washers for outer diameter: 3.3 to 4.8 mm

Standard connection for outer diameter: 5.0 to 6.5 mm

Remove the clamp for outer diameter: 6.5 to 7.0 mm

Reliable locking: Tighten with the nut of the zinc shell.

Internal locking hole design for longer plug life

Set contents: 1x male connector XL23MB plus 1x female connector XL23FB



ENOVA

Brand:	ENOVA
Series:	XL-Serie
Version (Plug / Chassis):	Cable Version
Connector type:	XLR, XLR female 3 pol, XLR male 3 pol
Number of contacts:	3
Gender (M / F):	Male plug, Female connector
Connector housing color:	Black
Cable diameter min. in mm:	Ø 3.3 mm
Cable diameter max. in mm:	Ø 7 mm
Wiring mode:	Solder contact
Material connector housing:	ZZNAL4-1
Material contact:	Phosphor Bronze
Working temperature minimum:	-30°
Working temperature maximum:	+80°
Classification flammability of plastics:	UL94HB
ROHS according to EN62321-1:	Yes
Country of origin:	China
Operating voltage (VAC.RMS):	< 50 V
Insulation resistance:	> 10 GΩ
Contact resistance:	≤ 3 mΩ
Applications:	DJ, Keyboard player, Lighting technician, Singer, Sound engineer
Markets:	Industry, Medical technology, Mechanical engineering, Devices construction, Plant construction