

Product information "4-piece XLR connector + chassis set as female + male 3 pin black solder version"

4-piece XLR cable plus installation set female and male with three contacts and a well-shaped and sturdy knob for a better user experience.

The 3-pin XLR Connector features a triple-positioned clamp to prevent the inner cable from being twisted and broken.

This removable clamp is designed for multiple cable types

Remove washers for outer diameter: 3.3 to 4.8 mm

Standard connection for outer diameter: 5.0 to 6.5 mm

Remove clamp for outer diameter: 6.5 to 7.0 mm

Reliable locking: tighten with the nut of the zinc shell.

Inner locking hole design for longer life of the connector.

Set Contents: 1x chassis connector male XL13MB plus 1x chassis connector female XL13FB plus 1x cable connector male XL23MB plus 1x cable connector female XL23FB.

ENOVA

Brand:	ENOVA
Series:	XL-Serie
Version (Plug / Chassis):	Cable Version, Chassis version
Connector type:	XLR, XLR female 3 pol, XLR male 3 pol
Number of contacts:	3
Gender (M / F):	Male plug, Female connector
Connector housing color:	Black
Cable diameter min. in mm:	Ø 3.3 mm
Cable diameter max. in mm:	Ø 7 mm
Wiring mode:	Solder contact
Material connector housing:	ZZNAL4-1
Material contact:	Phosphor Bronze
Working temperature minimum:	-30°
Working temperature maximum:	+80°
Classification flammability of plastics:	UL94HB
ROHS according to EN62321-1:	Yes
Country of origin:	China
Operating voltage (VAC.RMS):	< 50 V
Insulation resistance:	> 10 GΩ
Contact resistance:	≤ 3 mΩ
Applications:	DJ, Keyboard player, Lighting technician, Singer, Sound engineer
Markets:	Industry, Medical technology, Mechanical engineering, Devices construction, Plant construction

