



NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
10	O-RING	SILICON	BLACK	1	
9	CAP+BOOT	PA6+TPR	BK+GY	1	
8	CABLE CLAMP	POM	WHITE	1	
7	O-RING	SILICON	BLACK	1	
6	FEMALE PIN	PHOSPHOR BRONZE	SILVER	5	
5	INSULATOR	PA	BLACK	1	
4	LATCH	STAINLESS STEEL	TIN	1	
3	FIXED SHEET	STAINLESS STEEL	NICKEL	1	
2	PUSH BUTTON	ZZnAL4-1	NICKEL	1	
1	DIE CAST SHELL	ZZnAL4-1	Electro coating black	1	

DIMENSIONS ARE IN MILLIMETERS		APPROVED	DATE
UNLESS OTHERWISE SPECIFIED TOLERANCES		CHECKED	DATE
ANGLES = ±5°		DRAWN	DATE 2019-8-20
UP TO 6 = ±0.2		FILE NO.	
6-40 = ±0.4		ERP LINK:	
40-120 = ±0.6			
120-315 = ±1			
ABOVE 315 = ±1.6			
THIRD_ANGLE			
SCALE	1/1		

<b>Connector Distribution GmbH</b>			
TITLE <b>5PIN XLR FEMALE CONNECTOR</b>			
PART NO.	<b>XL25FB</b>	REV.	<b>A1</b>

**Notes:**  
 1. Remove O-ring used for cable O.D.: 3.3~4.8mm,  
 Standard connector used for cable O.D.: 5.0~7mm