

SIXPAR 300WMG



The IP65 outdoor rated SIXPAR 300WMG includes the same features as the standard SIXPAR 300IP model but with a special added White Marine Grade exterior coating designed for marine/coastal environment installations.

Featuring (18) 12W 6-in-1 RGBAW+UV LEDs producing a 23° beam angle, internal color and color chase macros, electronic strobe and variable dimming curve modes, manual and DMX-512 control, RDM (remote device management) support, dual yoke / floor stand, multiple unit power linking, rugged die-cast aluminum white marine grade coated exterior, flicker free operation for TV and FILM, and a multi-voltage universal auto switching power supply (110-250v).

FEATURES

- IP65 Outdoor Rated Par Luminaire
- Special White Marine Grade Exterior Coating
- Rugged Die-Cast Aluminum Exterior with Dual Yoke / Floor Stand
- (18) 12W 6-in-1 RGBAW+UV LEDs
- 23° Beam Angle
- 395nm UV Wavelength
- Electronic Strobe and Variable Dimming Curve Modes
- Manual and DMX-512 Control
- RDM (Remote Device Management) Support
- Multiple Unit Power Linking
- Proprietary IP Rated Power and Data In/Out Cables Attached
- Optional Extended Length Proprietary IP Rated Power and Data Linking Cables and In/Out Adapters Available



PRODUCT SPECIFICATIONS

SOURCE

(18) 12W 6-in-1 RGBAW+UV LEDs
 100,000 Hour Average LED Life*
 *May vary depending on several factors including but not limited to:
 Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

PHOTOMETRIC DATA

24,500 LUX 2,276 FC @3.3' (1m) (15° Full ON)

EFFECTS

Electronic Strobe
 Variable Dimming Curves Modes
 Internal Color and Color Chase Macros

CONTROL / CONNECTIONS

Manual and DMX-512 Control
 (4) DMX Channel Modes (6 / 7 / 8 / 12)
 (4) Button Touch LCD Menu Display
 Proprietary IP Rated 3pin DMX In/Out Cables Attached
 Proprietary IP Rated 3pin Power In/Out Cable Attached
 With Wired Digital Communication Network

SIZE / WEIGHT

Length: 14.4" (365mm)
 Width: 6.2" (157mm)
 Vertical Height: 14.4" (365mm)
 Weight: 19.2 lbs. (8.7 kg)

ELECTRICAL / THERMAL


AC 110-250V - 50/60Hz
 220W Max Power Consumption
 Multiple Unit Power Linking
 5°F to 113°F (-15°C to 45°C)
 UV Wavelength: 395nm

APPROVALS / RATINGS

CE | cETLus | IP65




PHOTOMETRIC DATA



| Distance | m | | ft | | m | | ft | | m | | ft | |
|--------------------|--------|-------|-------|-----|-------|-----|-------|------|-------|------|----|--|
| | 1 | 3.3 | 2 | 6.6 | 3 | 9.8 | 4 | 13.1 | 5 | 16.4 | | |
| 15° Beam Diameter | 0.4 | 1.3 | 0.64 | 2.1 | 0.85 | 2.8 | 1.05 | 3.4 | 1.32 | 4.3 | | |
| 25° Field Diameter | 0.45 | 1.5 | 0.88 | 2.9 | 1.33 | 4.4 | 1.77 | 5.8 | 2.21 | 7.3 | | |
| | lux | fc | lux | fc | lux | fc | lux | fc | lux | fc | | |
| RED LEDs | 4,750 | 441 | 1,308 | 122 | 430 | 40 | 315 | 29 | 199 | 18 | | |
| GREEN LEDs | 8,400 | 780 | 2,170 | 202 | 1,000 | 93 | 554 | 51 | 360 | 33 | | |
| BLUE LEDs | 9,520 | 884 | 2,490 | 231 | 1,185 | 110 | 662 | 61 | 425 | 39 | | |
| WHITE LEDs | 10,860 | 1,009 | 2,930 | 272 | 1,363 | 127 | 753 | 70 | 491 | 46 | | |
| AMBER LEDs | 3,130 | 291 | 823 | 76 | 351 | 33 | 197 | 18 | 127 | 12 | | |
| UV LEDs | 1,920 | 178 | 510 | 47 | 240 | 22 | 131 | 12 | 85 | 8 | | |
| FULL ON | 24,500 | 2,276 | 8,500 | 790 | 3,950 | 367 | 2,150 | 200 | 1,350 | 125 | | |

DIMENSIONAL DRAWINGS



*DRAWINGS NOT TO SCALE

ORDERING INFORMATION

| SIX076 | Sixpar 300WMG |
|----------------------|--|
| SIXPAR/2MDLC/WH | 3.3 ft. (1m) White IP Data Link Cable |
| SIXPAR/2MPLC/WH | 3.3 ft. (1m) White IP Power Link Cable |
| SIXPAR/2MDLC/WH | 6.6 ft. (2m) White IP Data Link Cable |
| SIXPAR/2MDLC/WH | 6.6 ft. (2m) White IP Power Link Cable |
| SIXPAR/5MDLC/WH | 16.4 ft. (5m) White IP Data Link Cable |
| SIXPAR/5MPLC/WH | 16.4 ft. (5m) White IP Power Link Cable |
| SIXPAR/10MDLC/WH | 32.8 ft. (10m) White IP Data Link Cable |
| SIXPAR/10MPLC/WH | 32.8 ft. (10m) White IP Power Link Cable |
| SIXPAR/20MDLC/WH | 65.6 ft. (20m) White IP Data Link Cable |
| SIXPAR/20MPLC/WH | 65.6 ft. (20m) White IP Power Link Cable |
| SIXPAR/DIAC/WH | White Data IN IP Adapter Cable |
| SIXPAR/DOAC/WH | White Data OUT IP Adapter Cable |
| SIXPAR/PIAC/WH | White Power IN IP Adapter Cable |
| SIXPAR/POAC/WH | White Power OUT IP Adapter Cable |
| SIXPAR/TERMINATOR/WH | White DMX Terminator End Cap |

Specifications subject to change without notice ©Elation Professional

