# Pixel Amp 200





200 Watt, 24V signal and power amplifier for Pixel Wash 40IP

**DATA SHEET** 



#### **KEY FEATURES**

P65 Rated

200W Power Amplifier for Pixel Wash 40IP

For use with Pixel Driver 170IP, Pixel Driver-1000IP, and

Pixel Driver-4000 V2

Can power/drive up to 8 Pixel Wash 40IP's in standard mode or 5 Pixel Wash 40IP's in HiPower mode

The **Pixel Amp 200** is a 200W power and signal amplifier for the Pixel Wash 40IP. This amplifier is designed to work in conjunction with the Elation Pixel Driver 170IP, Pixel Driver 1000IP or the Pixel Driver 4000V2.

Each **Pixel Amp 200** can power up to 8 Pixel Wash 40IP's in standard mode or 5 Pixel Wash 40IP's in HiPower mode. Up to 4 Pixel Amp 200's can be used in line for each driver output giving you the ability to control a total of 40 Pixel Wash 40IP's in standard mode or 25 Pixel Wash 40IP's in HiPower mode for each driver output.

The unit comes equipped with Power In, Data In/Out pigtail connections, and is IP65 rated, which protects the unit from the ingress of dust, as well as low pressure water jets sprayed from any direction.



# Pixel Amp 200





200 Watt, 24V signal and power amplifier for Pixel Wash 40IP

**SPECIFICATIONS** 

#### **CONTROL / CONNECTIONS**

Art-NET | sACN | Kling-NET Protocol Support

1 4-pin Power Input

1 4-pin Data Input

1 4-pin Data Output

### SIZE / WEIGHT

Length: 3.08" (78mm) Width: 9.18" (233mm) Height: 2.49" (63mm) Weight: 3.63lbs (1.65kg)

#### **ELECTRICAL**

Power Input: 100-240V, 50/60Hz Power Output: DC24V, 8.3A Max 200W Max Power Consumption

#### **APPROVALS / IP RATING**

CE | ETL | IP65 (Temporary Outdoor Use Only)





Specifications are subject to change without notice.



# Pixel Amp 200





200 Watt, 24V signal and power amplifier for Pixel Wash 40IP

## **UNIT DIMENSIONS**







## **ORDERING INFORMATION**

PIX685 / 1236200094	Pixel Amp 200
PIX672	Pixel Wash 40IP
PIX633	Pixel Driver 170IP
PIX301	Pixel Driver 1000IP
PIX259 / 1236200092	Pixel Driver 4000 V2
PIX300	Pixel BC2
PIX313	Pixel BC3
	additional cable lengths available

