

[Click to Print This Page](#)



E-VISION 4000 4K-UHD DIGITAL PROJECTOR



THE VISIONARIES CHOICE

E-Vision 4000 4K-UHD

3,300 ANSI / 3,800 ISO Lumens | Contrast Ratio: 500,000:1 Advanced Black. 1,300:1 native | Part Number: 121-804

Key Specifications:

Colour System:	Laser Phosphor
Display Type:	1 x 0.47" DarkChip 3™ DMD™
DMD Specification:	3840 x 2160
Aspect Ratio:	16x9
Fill Factor	
Key Features:	<p>Video & Graphics Processing</p> <ul style="list-style-type: none">• 2 x HDMI with HDCP• 3D support for Side by Side, Frame Packing and Top and Bottom formats• HDR processing• MEMC for enhanced motion performance• Synchronisation of active 3D glasses• DICOM simulation mode <p>Geometry Correction</p> <ul style="list-style-type: none">• Vertical Keystone correction adjustment Selectable 16:9, 4:3, Letterbox and Full Screen aspect ratios• Digital Zoom +10 ~ -10 <p>HDBaseT® Interface</p>

	<ul style="list-style-type: none"> Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable Allows the projector to be placed up to 100m from the source with low cost cabling HDBaseT® includes audio, Ethernet 100BaseT and RS232/IR control <p>Colour Processing</p> <ul style="list-style-type: none"> 6 Segment (WGYWGY) Phosphor wheel 8 Segment (BGYRBYR) Colour wheel 10-bit colour display (30 bits per pixel : 1,073,441,824 colours) Powerful seven point colour correction for accurate colour matching
--	--

Source Compatibility	Graphics standards up to 1920 x 1200 resolution at 60Hz. Input support for 4K-UHD, 3840 x 2160 and 4096 x 2160 at 60 Hz.
-----------------------------	---

Inputs/Outputs	Video & Computer			Communication & Control		
	Type	Connector	Qty	Type	Connector	Qty
	HDMI 2.1 VGA / Analog RGB HDBaseT USB Type A / (5V/2A) NOTE: The USB is to power external interfaces. Audio: Audio IN L+R Audio OUT (variable) Speaker	HDMI 15-pin D-Sub RJ45 USB Type A 3.5 mm jack 3.5 mm jack 10W speaker	2 1 1 1 1 1 1	LAN RS-232C USB (for Service) 3D Sync Out 12V Trigger NOTE: The HDBaseT and LAN ports are separate.	RJ45 9-pin D-sub Mini B VESA 3-PIN mini DIN 3.5mm jack	1 1 1 1 1

3D Formats Supported	Frame Packing Side By Side (half) Top and Bottom
-----------------------------	--

HDTV Formats Supported	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz) 1080i (50Hz, 60Hz) 720p (50Hz, 60Hz)
-------------------------------	---


Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz
-------------------------------	---

Bandwidth	
------------------	--

Remote Control	IR remote control, 2 x IR receivers
-----------------------	-------------------------------------

Automation Control	LAN control - Crestron RoomView® Connected LAN control - Crestron eControl LAN control - Extron LAN control to RS232 by Telnet HDBaseT communication Projector status email alerts PJ Link (Class1)
---------------------------	---

Colour Temperature	Warm / Normal / Cold
---------------------------	----------------------

Operation	
------------------	---

illumination Type	Laser Light Source										
Typical illumination Life	20,000 hours										
Lenses	<table border="1"> <thead> <tr> <th>Lens</th> <th>Part No.</th> <th>Optimised Focus Range*</th> <th>Lens Shift (Frame)</th> </tr> </thead> <tbody> <tr> <td>1.13 - 1.7:1</td> <td>N/A</td> <td>1.6m - 8m</td> <td>Vert: 0.60 (U) 0.60 (D) frame, Hor: 0.20 (L) 0.20 (R) frame</td> </tr> </tbody> </table>			Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	1.13 - 1.7:1	N/A	1.6m - 8m	Vert: 0.60 (U) 0.60 (D) frame, Hor: 0.20 (L) 0.20 (R) frame
	Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)							
1.13 - 1.7:1	N/A	1.6m - 8m	Vert: 0.60 (U) 0.60 (D) frame, Hor: 0.20 (L) 0.20 (R) frame								
<p>* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,</p>											
Lens Mount	Manual vertical and horizontal shift, with manual focus and zoom										
Mechanical Mounting	Front/Rear Front/Rear Ceiling Two adjustable front feet Ceiling Mount compatible chassis with 4 off M4 mounting holes										
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes										
Power Requirements	100-240VAC 50/60Hz single phase										
Power Consumption	Normal Mode (100%): 538W@240VAC, 570W@100VAC										
Thermal Dissipation	Normal Mode (typical): 1945 BTU/Hour @ 100VAC 1836 BTU/Hour @ 240VAC										
Fan Noise	Normal Mode (Typical): 35 dBA / Max: 37 dBA										
Operating/Storage Temperature Operating:	Operating: 0° to 40°C (32°F to 104°F) Storage: -10° to 60°C (14°F to 140°F)										
Operating Humidity	10% to 85% non-condensing										
Weight	12 kg / 26.45 lbs										
Dimensions	L: 405 mm W: 480 mm H: 180 mm L: 15.94 in W: 18.89 in H: 7.08 in										
Safety & EMC Regulations	UL/cUL, CB, CCC, FCC Class B, FDA, CE, UKCA, BSMI IEC 60825-1:2007 3R IEC 60825-1:2014 Class 1 IEC EN 62471-5 Risk Group 2 GB 7247.1-2012 RCM										
Accessories	<table border="1"> <thead> <tr> <th>Accessory</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td>Infrared Remote (replacement)</td> <td>122-755</td> </tr> </tbody> </table>			Accessory	Part No.	Infrared Remote (replacement)	122-755				
	Accessory	Part No.									
Infrared Remote (replacement)	122-755										
<p><i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i></p>											
Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings										

<p>User Guide</p>	<p>User Guides</p> <p>User Guides (German)</p> <p>User Guides (French)</p> <p>Laser Risk Group Document</p> <p>Control Protocol</p>
--------------------------	---



DIGITAL PROJECTION, LTD



Greenside Way, Middleton Manchester, UK

M24 1XX



T: +44.161.947.3300 | F: +44.161.684.7674



www.digitalprojection.co.uk



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770



A Delta Group Company

Specifications subject to change without notice.
©2022 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



Certificate Number 13629
ISO 9001