



DATA SHEET

3ft DisplayPort™ Male to HDMI® Male Adapter Cable - Black

Connect the DisplayPort output of a computer to the HDMI input of a HDTV or projector

OVERVIEW

This adapter cable is an ideal solution for connecting the DisplayPort output of a laptop to an HDTV or projector which accepts an HDMI input. This cable carries a digital audio/video signal, supports up to a 1080p resolution, and meets the requirements of high performance applications.

FEATURES

- Supports resolutions up to 1080p
- Directly connect a DisplayPort output to a HDMI input
- Carries a digital audio/video signal

ITEM DESCRIPTION

54326	6ft DisplayPort™ Male to HDMI® Male Adapter Cable - Black
54327	10ft DisplayPort™ Male to HDMI® Male Adapter Cable - Black
54324	15ft DisplayPort™ Male to HDMI® Male Adapter Cable - Black

ELECTRICAL SPECIFICATIONS

Voltage Rating: 30v

Conductor Resistance: @ 20°C maxInsulation Resistance: 10MΩ/km

Time Delay: 5.2ns/m (max)

Attenuation: 5.02dB@100-450MHz 7.69dB@1GHz

12.595dB@2GHz 17.495dB@3GHz 22.395dB@4GHz 27.295dB@5GHz 32.195dB@6GHz 37.095dB@7GHz

PHYSICAL SPECIFICATIONS

Operating Temperature: 0°C to 50°CStorage Temperature: -25°C to 70°C

- Approvals: CE

CONDUCTOR (2 CONDUCTOR, 5 PAIR):

Conductor: 30AWG (7/0.1TC)
Insulation: FM-PE, ID:0.8±0.05mm
Color: White/Brown, White/Red,
White/Orange, White/Green

White/Blue

Drain: 30AWG (7/0.1TC)HD-PE ID:0.56±0.05Shield: AL-Mylar WrapCoverage—100%

CONDUCTOR (5 CONDUCTORS):

Conductor: 30AWG (7/0.1TC)

Insulation: HD-PE, ID:0.56±0.05mmColor: Red/Orange/Yellow/Green/ White

OVERALL CABLE


Jacket: PVC

Shield: AL-Mylar—Coverage 100%

Braid—16/9/0.12

Drain: 2:30AWG (7/0.08 BC)

— OD: 6.5±0.2



C2G

A brand of legrand

c2g.com | legrandav.com USA 800.CABL.911

E: trg@c2g.com