
EB-760W



DATASHEET / BROCHURE



Project your vision, with an affordable, large screen display up to 150" that will enhance engagement, learning and productivity.

Whatever the size of class or meeting room, unrestricted and immersive presentations are possible with this bright, clear, compact and affordable display solution.

The EB-760W's bright image, scalable up to 150", is clearly visible from any angle and from a distance, and content can be easily shared or streamed directly from multiple devices for the perfect collaborative experience.

The EB-760W's ultra short throw lens allows safe, discreet positioning close to the display, enabling presenters free access to perform without casting shadows.

With 4,100 lumens Colour Light Output and Epson 3LCD technology, the display is bright and vibrant up-to 150", clearly visible from all angles and from a distance. The experience is immersive and user-friendly.

Projection also enables flexible display sizes, scalable from 49-150", display sizes can be optimised for each room with one familiar product and at a fixed cost

Versatile wired and wireless connectivity options, including screen mirroring via Miracast[™], allow participants to effortlessly share content from their PCs or mobile devices. With a connected optional Epson visualiser, documents, presentations or 3D objects can be viewed with incredible detail.

Unlike a flat-panel display, there is no heavy, breakable, glass panel to create disruptive, reflected blind spots at certain angles, and teachers are not subjected to LCD panel direct blue light radiation, believed to damage eyes. Paired with a hygienic, antibacterial whiteboard, teachers can annotate presentations with dry-wipe pens, or to save energy, simply use the whiteboard with the display turned off.

KEY FEATURES

- Scalable HD display for any room 53-150" UST display for unrestricted viewing (no shadows/reflections)
- Bright and energy efficient laser 4,100lm CLO with 3LCD technology for brighter colours at only 205W
- Effortless connectivity options Auto-on, wired / wireless display with USB 2A output for smart sticks
- Simple to use and built to last Virtually maintenance free with 5-year, 12,000hr warranty
- Document camera compatibility Create and record a live, totally immersive lesson or presentation



PRODUCT SPECIFICATIONS

TECHNOLOGY		
Projection System	3LCD Technology, RGB liquid crystal shutter	
LCD Panel	0.59 inch with C2 Fine	
IMAGE		
Color Light Output	4,100 Lumen- 2,800 Lumen (economy) In accordance with IDMS15.4	
White Light Output	4,100 Lumen - 2,800 Lumen (economy) In accordance with ISO 21118:2020	
Resolution	WXGA	
High Definition	HD ready	
Aspect Ratio	16:10	
Contrast Ratio	Over 2,500,000 : 1	
Light source	Laser	
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco	
Keystone Correction	Manual vertical: ± 3 °, Manual horizontal ± 3 °	
Colour Video Processing	10 Bits	
2D Vertical Refresh Rate	100 Hz - 120 Hz	
Colour Reproduction	Upto 1.07 billion colours	
	·	
OPTICAL		
Throw Ratio	0.27 - 0.37:1	
Zoom	Digital, Factor: 1 - 1.35	
Lens	Optical	
Screen Size	60 inches - 150 inches	
Projection Lens F Number	1.6	
Projection Lens Focal Length	3.7 mm	
Projection Lens Focus	Manual	
Offset	6:1	
CONNECTIVITY		
Interfaces	USB 2.0-A (2x), RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE	
	802.11a/b/g/n/ac, VGA in (2x), VGA out, HDMI in (3x), Composite in, Miracast, Jack plug out,	
	Jack plug in (3x), USB 2.0 Type B (Service Only), Wi-Fi Direct, Microphone input	
Epson iProjection App	Ad-Hoc / Infrastructure	
Network Protocol	HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink	
ADVANCED FEATURES		
Security	Kensington lock, Control panel lock, Padlock, Security cable hole, Wireless LAN unit lock,	
······································	Wireless LAN security, Password protection	
Other features	A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC	
	compatible, Customizable user logo, Digital zoom, Direct Power on/off, Document Camera	
	Compatible, Email notification, Home Screen, Horizontal and vertical keystone correction,	
	Image Shift, JPEG Viewer, Long light source life, Network projection, OSD copy function, PC	
	Free, Power on button, Quick Corner, Schedule Function, Screen Mirroring, Ultra-wide display	
	(16:6), Web Control, Web Remote, Wireless LAN capable, iProjection App	
Video Color Modes	Blackboard, Cinema, Dynamic, Presentation, sRGB	
Projector control	via: Crestron Integrated Partner, Crestron RoomView, Extron IP Link, AMX Device Discovery,	
	Control4 Simple Device Discovery Protocol	

EB-760W

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Quick Start Guide



PRODUCT SPECIFICATIONS

EB-760W

GENERAL		
Power consumption	197 Watt - On mode power consumption (Normal)	
	263 Watt (Peak), 199 Watt (Eco), 0.5 Watt (Energy saving standby)	
Heat Dissipation	895 BTU/hour (max)	
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz	
Product dimensions	356 x 395 x 133 mm (Width x Depth x Height)	
Product weight	5.9 kg	
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)	
Supported Temperature	Storage -10° C - 60° C	
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%	
	If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could break and cause the projector to drop from the ceiling.	
	If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.	
Included Software	EasyMP Multi PC Projection, Epson Projector Content Manager, Epson Projector Managemen	
Options	Air filter, Ceiling mount, Connection and control box, External Speaker, Safety wire set,	
	Visualiser camera, WP System - ELPWP10, Wall mount, Wireless LAN unit, Wireless	
	transmitter - ELPWT01	
Loudspeaker	16 Watt	
Room Type / Application	Meeting room / Classroom	
Positioning	Ceiling Mounted, Desktop, Wall Mounted	
Colour	White	
OTHER		
Warranty	60 months Carry in or 12,000 h	
	Optional warranty extension available	



OPTIONAL ACCESSORIES

- Control and Connection Box ELPCB03 V12H927040DA
- Active Speakers (2 x 15W) ELPSP02 V12H467040DA
- Wall Mount ELPMB62 EB-7xx / EB-8xx V12HA06A06
- Adapter ELPAP11 Wireless LAN (5GHz) V12H005A01
- Air Filter ELPAF60 EB-7XX / EB-L2xx Series V13H134A60
- Ceiling Mount (White) ELPMB23 V12H003B23
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14
- Control and Connection Box ELPCB03 V12H927040

LOGISTICS INFORMATION

ѕки	V11HA81080
EAN code	8715946715285
Country of Origin	Philippines
Layer	2 Units

SYNC AV d.o.o. Celovška cesta 172 1000 Ljubljana Slovenia info@sync-av.com

* Warranty offers are not available for all countries. Please contact your local Epson representative.

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min) Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

EB-760W

EPSON[®]

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

⁽Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742